



THIS INFORMATION IS CONFIDENTIAL AND IS DISCLOSED TO YOU ON CONDITION THAT NO FURTHER DISCLOSURE IS MADE BY YOU TO OTHER THAN PEXON PERSONNEL WITHOUT WRITTEN AUTHORIZATION FROM PEXON LTD.

DWN No.: C-10110041611



Item	Part name	Q'ty/Ea'	Material	Finish
1	HSG	1	High temp.Plastic UL94 V-0 Color Black	_____
2	Body	4	Leaded Brass	Au 0.1um plating Ni 1.4um
3	Plunger	4	Leaded Brass	Au 0.4um plating Ni 1.4um
4	Spring	4	Stainless steel wire	_____
5				

Table 1 Mechanical performance		
Working height	5.50mm	100±20gf <2.1>
Durability	10000cycle	

Notes:

- Dimensions shall be interpreted per ASME Y14.5M.
- Mechanical performance (See the table 1)
<2.1>The force is the average of forces obtained when plunger goes downwards and upwards.
<2.2>Warning: Working height are not permitted to be less than Min working height.
- Electrical performance
Resistance: 30mOhm Max.
Current rating: 2.0A
- RoHS compliant.

10110041611

PART NUMBER

Top-Link Electronics Ltd.		Type	Customer drawing	Unit	mm	Weight	_____
TOLERANCES UNLESS OTHER SPECIFIED		DWN:	Caiwanlu	APVD:		Pexon	
0. = ± -		CHK:		REL:			
0.0 = ± 0.15		Name				Pogo pin connector	
0.00 = ± 0.10		Scale	1:1	Size	A4	DWG No.	C-10110041611
0.000 = ± -						Page	1/1
Angle: ±1°						Rev.	1
SURF TEXTURE: REMOVE BURRS. BREAK SHARP EDGES R0.05 MAX.DO NOT SCALE PRINT.							

1	NEW	2016/03/31
Rev.	Revision record.	Date.

DIST

DIST



PEXON

E-mail: sale@pinconnector.com

WhatsApp: +86-13361867201

www.pinconnector.com