



| | |
|-------------------------------------------------------------------------------|---------------------|
| 技术要求 (Technical Specifications) : | |
| 额定电流 (Current Rating) | 3A |
| 额定电阻 (Rated Resistance) | 100 milliohm max |
| 满行程 (Full Stroke) | 5.3mm |
| 额定行程 (Rated Stroke) | 3.5mm |
| 额定弹力 (Spring Force) | 113±35gf@load 3.5mm |
| 材质 (Materials) : | |
| 针杆 (Plunger) | BeCu ,gold-plated |
| 针管 (Barrel) | Br,gold-plated |
| 弹簧 (Spring) | SWP ,gold-plated |
| 成品型号 (Product Type) : | |
| <p>CH165-H-4G(B)</p> <p>系列 规格 头型 弹力 电镀 特性 针杆 材质</p> <p>订购举例:CH165-H-4G(B)</p> | |

| | |
|----------|----------|
| CH165-A | CH165-B |
| | |
| CH165-D | CH165-E2 |
| | |
| CH165-F | CH165-H |
| | |
| CH165-J | CH165-Q1 |
| | |
| CH165-Q2 | CH165-T2 |
| | |



PEXON

E-mail: sale@pinconnector.com

WhatsApp: +86-13361867201

www.pinconnector.com